

CHAMELEON Dissolvable Plug

CHAMELEON

CHAMELEON Dissolvable Plug is the most versatile product in Vertechs dissolvable product line. It can be customized to either a bullhead or a flow-thru or ball-in-place design. The dual slips hold high differential pressure from both above and below. The game-changing CHAMELEON Dissolvable Plug, manufactured using proprietary fully dissolvable materials, will dissolve downhole and then a full-bore access can be achieved. CHAMELEON Dissolvable Plug can be set by conventional wireline or hydraulic setting tools. For application flexibility, in planning the CHAMELEON system dissolving phase, the dissolving rate (ROD) can be customized on a case by case basis to meet operational requirements.

FEATURES:

- Bi-directional slips
- 10,000 psi differential pressure rating
- Designed for temperatures from 104°F to 302°F
- Proprietary anti-preset feature
- Customizable ROD (Rate of Dissolution)
- Setting with standard setting tools
- Dissolvable packing elements
- Compatible with high API casing grades (Q125)



SPECIFICATIONS:

Casing Size	Weight (lb/ft)	Casing Grade
3.5"	10.2	
4.5"	12.6, 13.5-15.1	N80 P110
5"	20.3-23.2	Q125
5.5"	17.0-23.0, 26.0-26.8	