VERTECHS CHAMELEON

Chameleon Dissolvable Plug

Vertechs Chameleon Dissolvable Plug is a customized dissolvable plug with dual slips which could hold high differential pressure from both above and below. It can be converted to ball-in-place, ball drop, caged ball and bull-headed bridge plug configurations. It is manufactured using proprietary customized high strength fully dissolvable materials that could dissolve downhole after stimulation, and then a full-bore access can be achieved. The plug can be set by conventional wireline or hydraulic setting tools. For application flexibility, in planning the plug dissolving phase, the dissolving rate (ROD) can be customized on a case-by-case basis and designed based on the operational requirements.

FEATURES

- Bi-directional slips
- Pressure rating up to 15,000 psi
- Temperature rating up to 302°F
- Customizable ROD (Rate of Dissolution)
- Setting with standard setting tools
- Dissolvable packing elements
- Compatible with high API casing grades (Q125 & 140V)



VERTECHS

SPECIFICATIONS

Casing Size	Casing Weight (lb/ft)	Casing Grade
3.5"	10.2	N80 P110 Q125 140V
4.5"	12.6, 13.5 - 15.1	
5.0"	20.3 - 23.2	
5.5"	17.0 - 23.0, 26.0 - 26.8	

Contact Us

engineering@vertechs.com

Chengdu | Dammam | Houston | Calgary | Hong Kong

Disclaimer

This document and any files transmitted with it are for use between Vertechs Group and external partners related to the Group's business. Unauthorized use is prohibited, and the dissemination, copying, or distribution of this document and its contents is strictly forbidden until the information becomes public or loses its commercial value. Violators will be held legally responsible.

2025 Copyright © Vertechs Group. All rights reserved. www.vertechs.com