

## Wizard Ultra Dissolvable Plug

Designed to withstand extreme conditions of high pressure and high temperature (HPHT), rating up to 15,000 psi and 350°F above. These frac plugs may also feature unique geometries and surface treatments, such as enhanced coatings or textures, that improve their performance and durability under corrosive and acidic environments.

### FEATURES

- Temperature rating up to 350°F
- Pressure rating up to 15,000 psi
- Acid frac & proppant frac application
- Coated variant available
- Ball-in-place and ball-drop convertible
- Run with standard Baker wireline or hydraulic setting tools



### SPECIFICATIONS

Casing Size	Casing Weight (lb/ft)	Casing Grade
3.5"	9.2	N80 P110 Q125 140V
4.5"	11.6 - 15.1	
5"	18.0 - 24.2	
5.5"	17.0 - 23.0, 26.0 - 26.8	

6"	23.2 - 24.5	
----	-------------	--



## Contact Us

[engineering@vertechs.com](mailto:engineering@vertechs.com)

Chengdu | Dammam | Houston | Calgary | Hong Kong

**Disclaimer :**

This document and any files transmitted with it are for use between Vertechs Group and external partners related to the Group's business. Unauthorized use is prohibited, and the dissemination, copying, or distribution of this document and its contents is strictly forbidden until the information becomes public or loses its commercial value. Violators will be held legally responsible.

2025 Copyright © Vertechs Group. All rights reserved.  
[www.vertechs.com](http://www.vertechs.com)