

## iRCD

Vertechs iRCD is an all-electric intelligent RCD solution for MPD and UBD. As oil and gas exploration advances into deep-sea, deep-earth, high-pressure, and unconventional reservoirs, traditional RCDs face increasing challenges in deployment, operation, and maintenance. iRCD features a non-decoupled electric locking mechanism to prevent wear from installation misalignment, and a high-pressure-resistant, self-lubricating dynamic seal assembly, eliminating the need for external hydraulic cooling. These innovations simplify setup, extend seal lifespan, reduce operational costs, and save installation time.

## FEATURES

- Self-lubricating system, no additional cooling required
- Self-positioning deployment with dedicated insertion and retrieval tools
- Applicable to land rigs, modular rigs, and jack-up rigs



## SPECIFICATIONS

API Standard	API 16RCD	Actuator	Electric (Low-voltage DC, Explosion-proof, Non-decoupled)
Max. Static Pressure	5,000 psi	Max. Dynamic Pressure	2,500 psi
Bearing Assembly	8 1/4 in	Bottom Flange	13 5/8 in

Hosing Max. Outlet	7 1/16 in	RPM	0 – 200 rpm
Hosing Height	46 – 53 in	Weight	1.5 – 3 T
Packing Elements	Single / Dual	Cooling	Self-lubricating

## Contact Us

[engineering@vertechs.com](mailto:engineering@vertechs.com)

---

**Chengdu | Dammam | Houston | Calgary | Hong Kong**

---

### Disclaimer :

This document and any files transmitted with it are for use between Vertechs Group and external partners related to the Group's business. Unauthorized use is prohibited, and the dissemination, copying, or distribution of this document and its contents is strictly forbidden until the information becomes public or loses its commercial value. Violators will be held legally responsible.

2025 Copyright © Vertechs Group. All rights reserved.  
[www.vertechs.com](http://www.vertechs.com)