

IPC-MPD

Case Study 1: MPD and Workover in an Ultra-Deep Oil Well with Slimhole

OVERVIEW

- Operation Time: May – July 2024
- Operation Area: Northwest China
- Reservoir Type: Oil Well (Ultra-Deep, Slimhole)
- Mud Density: 2.16 – 2.20 g/cm³ (18.02 – 18.36 ppg)
- Mud Type: OBM
- ECD Window: <0.05 g/cm³ (<0.42 ppg)
- Casing Runs: 1 (6 in)
- Well Depth: 6,260m – 8,100m (20,541 ft – 26,575 ft)
- Applied in: MPD, Workover



RESULTS

- Completion of MPD and well intervention operations in an ultra-deep well exceeding 8,000m (26,247 ft)
- Simulation of the wellbore pressure window through real-time and high-precision hydraulic modeling enabled precise pressure control during both circulation (drilling) and non-circulation phases (tripping and connections) to meet formation pressure requirements

Case Study 2: MPD and Cementing in a High-Pressure, High-Production Gas Well

OVERVIEW

- **Operation Time:** April – October 2023
- **Operation Area:** Southwest China
- **Reservoir Type:** Gas Well (High-Pressure, High-Production)
- **Mud Density:** 2.12 – 2.25 g/cm³ (17.70 – 18.77 ppg)
- **Mud Type:** OBM
- **ECD Window:** <0.1g /cm³ (<0.83 ppg)
- **Casing Runs:** 2 (8 1/2 in, 6 in)
- **Well Depth:** 3,410m – 5,072m (11,190 ft – 16,632 ft)
- **Applied in:** MPD, Cementing



RESULTS

- Ensured safe operations in the high-pressure gas well
- Successfully resolved more than 8 downhole kicks and loss events across 2 sections
- Achieved 9 days of constant bottomhole pressure circulating operations during 14 gas discharge operations, reducing NPT and shortening the well completion cycle

Case Study 3: MPD and Cementing in a Gas Well in a Fractured Reservoir with High H₂S

OVERVIEW

- **Operation Time:** February – July 2021
- **Operation Area:** Southwest China
- **Reservoir Type:** Gas Well in a Fractured Reservoir (High H₂S)
- **H₂S Content:** >30,000 ppm
- **Mud Density:** 2.32 – 2.40 g/cm³ (19.37 – 20.03 ppg)
- **Mud Type:** WBM
- **ECD Window:** <0.1 g/cm³ (<0.83 ppg)
- **Casing Runs:** 2 (8 1/2 in, 6 in)
- **Well Depth:** 4,804m – 6,210m (15,758 ft – 20,379ft)
- **Applied in:** MPD, Cementing



RESULTS

- Precise bottomhole pressure control enabled safe operations in the well with high H₂S content
- Significantly improved drilling efficiency and cementing quality
- New record set: 250m (820 ft) deeper than the planned measured depth and the faster exploration well

Contact Us

engineering@vertechs.com

Chengdu | Dammam | Houston | Calgary | Hong Kong

Disclaimer :

This document and any files transmitted with it are for use between Vertechs Group and external partners related to the Group's business. Unauthorized use is prohibited, and the dissemination, copying, or distribution of this document and its contents is strictly forbidden until the information becomes public or loses its commercial value. Violators will be held legally responsible.

2025 Copyright © Vertechs Group. All rights reserved.
www.vertechs.com